







# A/C HOSE

# AC04/05

## 4 OR 5 LAYERS




- TUBE : BLACK,SMOOTH,SPECIAL SYNTHETIC RUBBER WITH VERY LOW GAS PERMEATION.
- REINFORCEMENT : 2 HIGH TENSILE SYNTHETIC TEXTILE BRAID.
- COVER : SPECIAL SYNTHETIC PIN-PRICKED RUBBER,RESISTANT TO HIGH TEMPERATURE APPLICATIONS.
- APPLICATION : FOR THE TRANSFER OF R134A GAS AND LIQUID,IN AIR CONDITIONING SYSTEMS FOR AUTOMOTIVE INDUSTRY.
- TEMPERATURE RANGE : -40°C~+100°C / -40°F~+212°F

TYPE	SIZE		 ID (mm)		 OD (mm)		 WP		 BP		 BR/r	 L
	Dash Size	inch	min	max	min	max	bar	psi	bar	psi	mm	max/m
<b>4 LAYERS</b>												
AC04-08	-06	5/16	7.8	8.6	14.8	15.6	27	390	137	2000	78	50/100
AC04-11	-08	13/32	9.5	10.5	16.7	17.5	27	390	137	2000	88	50/100
AC04-13	-10	1/2	12.5	13.5	20.6	21.4	27	390	137	2000	107	50/100
AC04-16	-12	5/8	14.7	15.7	22.5	23.5	27	390	137	2000	118	50/100
<b>5 LAYERS</b>												
AC05-08	-06	5/16	7.8	8.6	14.8	15.6	27	390	137	2000	78	50/100
AC05-11	-08	13/32	9.5	10.5	16.7	17.5	27	390	137	2000	88	50/100
AC05-13	-10	1/2	12.5	13.5	20.6	21.4	27	390	137	2000	107	50/100
AC05-16	-12	5/8	14.7	15.7	22.5	23.5	27	390	137	2000	118	50/100

MARKING/TRANSFER TAPE,EMBOSSSED OR INK JET

 A/C HOSE R-134A(\*\*\*) (DN\*\*mm) W.P.\*\*BAR/\*\*PSI \*Q/\*\*\*\*(YEAR)

NORMS		COLOUR	 BLACK
-------	--	--------	--