


BLACK AIR HOSE

BF300

300PSI



TUBE : SPECIAL SYNTHETIC RUBBER.

REINFORCEMENT : HIGH TENSILE SYNTHETIC TEXTILE.

COVER : ABRASION AND WEATHER RESISTANT SPECIAL BLACK SYNTHETIC RUBBER.

APPLICATION : USED IN LOW-PRESSURE AIR CONVENING SYSTEMS.

TEMPERATURE RANGE : -40°C~+100°C / -40°F~+212°F

TYPE	SIZE	ID (mm)		OD (mm)		WP		BP		W	L
		inch	min	max	min	max	bar	psi	bar	psi	g/m
BF300-06	1/4	6.2	7.0	12.7	14.3	20	300	60	900	180	25/50
BF300-08	5/16	7.7	8.5	14.7	16.3	20	300	60	900	260	25/50
BF300-10	3/8	9.3	10.1	16.7	18.3	20	300	60	900	310	25/50
BF300-13	1/2	12.6	13.8	24.5	26.5	20	300	60	900	460	25/50
BF300-16	5/8	15.6	16.8	24.4	26.4	20	300	60	900	510	25/50
BF300-19	3/4	18.6	19.8	28.8	30.8	20	300	60	900	660	25/50
BF300-25	1	24.6	25.2	36.5	38.5	20	300	60	900	810	25/50
BF300-32	1-1/4	31.8	32.4	42.8	45.2	20	300	60	900	1090	20/40
BF300-38	1-1/2	37.8	38.4	50.8	53.2	20	300	60	900	1470	20/40
BF300-51	2	50.8	51.4	63.8	66.2	20	300	60	900	2060	20/40


OPTIONS



MSHA

MARKING/TRANSFER TAPE,EMBOSSSED OR INK JET

Wojun AIR HOSE BF300(***) (DN**mm) W.P.**BAR/**PSI *Q/****(YEAR)

		COLOUR	 BLACK
--	--	--------	--