

BLACK AIR HOSE

BF400

400PSI



TUBE : SPECIAL SYNTHETIC RUBBER.

REINFORCEMENT : HIGH TENSILE SYNTHETIC TEXTILE.

COVER : ABRASION AND WEATHER RESISTANT SPECIAL BLACK SYNTHETIC RUBBER.

APPLICATION : USED IN LOW-PRESSURE AIR CONVENING SYSTEMS.

TEMPERATURE RANGE : -40°C~+100°C / -40°F~+212°F

TYPE	SIZE	 ID (mm)		 OD (mm)		 WP		 BP		 W	 L
		min	max	min	max	bar	psi	bar	psi	g/m	max/m
BF400-06	1/4	6.2	7.0	12.7	14.3	28	400	84	1200	180	25/50
BF400-08	5/16	7.7	8.5	14.7	16.3	28	400	84	1200	260	25/50
BF400-10	3/8	9.3	10.1	16.7	18.3	28	400	84	1200	310	25/50
BF400-13	1/2	12.6	13.8	24.5	26.5	28	400	84	1200	460	25/50
BF400-16	5/8	15.6	16.8	24.4	26.4	28	400	84	1200	510	25/50
BF400-19	3/4	18.6	19.8	28.8	30.8	28	400	84	1200	660	25/50
BF400-25	1	24.6	25.2	36.5	38.5	28	400	84	1200	810	25/50
BF400-32	1-1/4	31.8	32.4	42.8	45.2	28	400	84	1200	1090	20/40
BF400-38	1-1/2	37.8	38.4	50.8	53.2	28	400	84	1200	1470	20/40
BF400-51	2	50.8	51.4	63.8	66.2	28	400	84	1200	2060	20/40

OPTIONS



MSHA

MARKING/TRANSFER TAPE,EMBOSSSED OR INK JET

 **AIR HOSE BF400(**)(DN**mm) W.P.**BAR/**PSI *Q/****(YEAR)**

		COLOUR	 BLACK
--	--	--------	--