

YELLOW AIR HOSE

400 PSI



TUBE : OIL MIST RESISTANT SYNTHETIC RUBBER.
 REINFORCEMENT : MULTIPLE LAYERS OF SPIRAL SYNTHETIC YARN.
 COVER : YELLOW AND ABRASION RESISTANT RUBBER.
 APPLICATION : AIR/WATER HOSE FOR USING IN DEMANDING ENVIRONMENTS SUCH AS MINING, CONSTRUCTION AND INDUSTRIAL APPLICATIONS.
 TEMPERATURE RANGE : -40°C to +100°C (-40°F to +212°F)

TYPE	SIZE	 ID (mm)		 OD (mm)		 WP		 BP		 W	 L
		min	max	min	max	bar	psi	bar	psi	g/m	max/feet
YA06-3-F-4	1/4"	6.2	7.0	12.7	14.3	28	400	84	1200	180	50/100
YA08-3-F-4	5/16"	7.7	8.5	14.7	16.3	28	400	84	1200	260	50/100
YA10-3-F-4	3/8"	9.3	10.1	16.7	18.3	28	400	84	1200	310	50/100
YA12-3-F-4	1/2"	12.6	13.8	21.8	23.8	28	400	84	1200	460	50/100
YA16-3-F-4	5/8"	15.6	16.8	24.4	26.4	28	400	84	1200	510	50/100
YA19-3-F-4	3/4"	18.6	19.8	28.8	30.8	28	400	84	1200	660	50/100
YA25-3-F-4	1"	24.6	25.2	36.5	38.5	28	400	84	1200	810	50/100
YA32-3-F-4	1-1/4"	31.8	32.4	42.8	45.2	28	400	84	1200	1090	50/100
YA38-3-F-4	1-1/2"	37.8	38.4	50.8	53.2	28	400	84	1200	1470	50/100
YA51-3-F-4	2"	50.8	51.4	63.8	66.2	28	400	84	1200	2060	50/100
YA63-3-F-4	2-1/2"	63.8	65	74.9	77.9	28	400	84	1200	2000	50/100
YA76-3-F-4	3"	75.9	77.1	91.5	94.5	28	400	84	1200	2450	50/100
YA89-3-F-4	3-1/2"	88.9	90.1	104.5	107.5	28	400	84	1200	3560	50/100
YA102-3-F-4	4"	101.8	103	117.5	120.5	28	400	84	1200	3840	50/100

OPTIONS



EPDM COVER

MSHA

MARKING/TRANSFER TAPE,EMBOSSSED OR INK JET



AIR HOSE(***)(DN**mm) W.P.**BAR/**PSI *Q/****(YEAR)

		COLOUR	 YELLOW
--	--	--------	---