

R134a 4-LAYER A/C HOSE

A20/A10

4 LAYERS (SAE J2064 TYPE E)










TUBE : BLACK,SMOOTH,SPECIAL SYNTHETIC RUBBER WITH VERY LOW GAS PERMEATION.
 REINFORCEMENT : 1 HIGH TENSILE SYNTHETIC TEXTILE BRAID.
 COVER : SPECIAL SYNTHETIC PIN-PRICKED RUBBER,RESISTANT TO HIGH TEMPERATURE APPLICATIONS.
 APPLICATION : FOR THE TRANSFER OF R134A GAS AND LIQUID,IN AIR CONDITIONING SYSTEMS FOR AUTOMOTIVE INDUSTRY.

TEMPERATURE RANGE : -40°C~+135°C / -40°F~+275°F


PERMEABILITY(KG / M2 / YEAR) 1.6

THICK WALL A20 / THIN WALL A10

TYPE	SIZE		 ID (mm)		 OD (mm)		 Wall Thickness (mm)	 WP	 BP	 BR/r	 L
	Dash Size	inch	min	max	min	max	mm	W.P.	B.P.	mm	max/m
E-A20-8	8.2	5/16	7.8	8.6	17.8	18.8	5.3±0.4	3.5	20	55	50/100
E-A20-10.5	10.5	13/32	10.1	10.9	22.0	23.0	6±0.4	3.5	20	85	50/100
E-A20-13	13	1/2	12.6	13.4	22.5	23.5	5±0.4	3.5	20	90	50/100
E-A20-16	16	5/8	15.5	16.5	27.4	28.6	6±0.4	3.5	20	105	50/100
E-A10-6	6.5	1/4	6.1	6.7	13.1	13.7	3.5±0.4	3.5	24	55	50/100
E-A10-8	8.2	5/16	7.9	8.5	14.8	15.6	3.5±0.4	3.5	24	55	50/100
E-A10-9	9.5	3/8	9.2	9.8	16.4	17	3.6±0.4	3.5	24	65	50/100
E-A10-10	10.5	13/32	10.2	10.8	18.3	19.1	4.1±0.4	3.5	24	75	50/100
E-A10-11	11.5	7/16	11.2	11.8	18.1	18.9	3.5±0.4	3.5	24	75	50/100
E-A10-13	13.2	1/2	12.9	13.5	20.4	21.2	3.8±0.4	3.5	23	75	50/100
E-A10-14	14.5	9/16	14.2	14.8	21.6	22.4	3.8±0.4	3.5	23	75	50/100
E-A10-15	15.2	5/8	14.8	15.6	22.3	23.3	3.8±0.4	3.5	22	85	50/100
E-A10-19	19	3/4	18.5	19.5	27.9	29.1	4.8±0.4	3.5	24	105	50/100
E-A10-25	25	1	24.7	25.3	34.7	35.3	5.0±0.2	3.5	24	110	50/100
E-A10-28	28.5	9/8	28.2	29.1	39.2	39.8	5.5±0.2	3.5	24	110	50/100
E-A10-32	32	1-1/4	31.7	32.3	42.7	43.3	5.5±0.2	3.5	24	115	50/100

MARKING/ INK JET

 SAE J2064 A/C HOSE R-134A(***)(DN**mm) W.P.**BAR/**PSI *Q/***(YEAR)135°C

NORMS:	SAE J2064 TYPE E	COLOUR	 BLACK
--------	---------------------	--------	--