

PVC OIL HOSE

2 Textile Braid



TUBE : HYDRAULIC OIL RESISTANT SPECIAL SYNTHETIC RUBBER.

REINFORCEMENT : 2 HIGH TENSILE SYNTHETIC TEXTILE BRAID.

COVER : OIL, ABRASION, OZONE AND WEATHER RESISTANT SPECIAL SYNTHETIC RUBBER WITH PVC.

APPLICATION : FOR A MAXIMUM AROMATIC CONTENT OF 25% (NAPHTHAS, GAS OILS, FUEL OILS, KEROSENE, ETC) ON REQUEST, IT CAN BE SUPPLIED WITH A COPPER CABLE FOR ELECTROSTATIC.

TEMPERATURE RANGE : -20°C~+82°C / -4°F~+180°F

TYPE	SIZE		 ID (mm)		 OD (mm)		 WP		 BP		 BR/r	 W	 L
	Dash Size	inch	min	max	min	max	bar	psi	bar	psi	mm	kg/m	max/m
PO-16	-10	5/8	15.6	16.5	27.5	28.5	30	435	90	1305	220	0.38	50
PO-19	-12	3/4	18.4	19.6	30.2	31.4	30	435	90	1305	250	0.41	50
PO-25	-16	1	24.2	26.2	37.0	38.6	25	363	75	1088	300	0.59	50
PO-32	-20	1-1/4	31.0	33.0	43.0	44.6	20	290	60	870	350	0.70	40
PO-38	-24	1-1/2	37.8	38.8	47.5	50.0	17	247	51	740	360	0.84	40
PO-41	-26	1-10/16	41.8	42.8	51.5	54.0	15	218	45	653	370	0.96	40
PO-44	-28	1-3/4	44.8	45.8	54.5	57.0	15	219	45	653	380	1.10	40
PO-51	-32	2	50.8	51.8	60.5	63.0	10	145	30	435	400	1.36	40
PO-57	-36	2-1/4	57.0	58.5	66.5	69.0	9	131	27	392	500	1.44	40

MARKING/TRANSFER TAPE, EMBOSSED OR INK JET

 PVC OIL (**)(DN**mm) W.P.**BAR/**PSI *Q/***(YEAR)

		COLOUR	   			
			GREEN	BLACK	BLUE	RED