

ULTRA-HIGH PRESSURE HOSE

UH-2740D

6 Steel Wire Spiral










TUBE : POLYOXYMETHYLENE.

REINFORCEMENT : SIX SPIRAL LAYERS OF MAXIMUM TENSILE STEEL WIRE.

COVER : POLYAMIDE.

APPLICATION : FOR HYDRODEMOLITION, WATER JET CUTTING, SHIP WASHDOWN AND INDUSTRIAL HIGH-PRESSURE CLEANING.




TEMPERATURE RANGE : -10°C~+70°C / 14°F ~ 158°F

TYPE	SIZE		 ID (mm)		 OD (mm)	 WP		 BP		 BR/r	 W	 L
	Dash Size	inch	min	max	max	bar	psi	bar	psi	mm	g/m	max/m
UH-2740D-04	-025	5/32	3.4	4.4	12.5	3000	43500	7800	113100	120	400	50/100
UH-2740D-05	-03	3/16	4.3	5.3	13.7	2800	40600	7000	101500	200	470	50/100
UH-2740D-08	-05	5/16	7.3	8.3	17.7	2500	36250	6250	90625	200	830	50/100
UH-2740D-13	-08	1/2	12.2	13.2	27.5	2000	29000	5000	72500	300	1850	50/100



MARKING / INK JET

WOJUN ULTRA-HIGH PRESSURE HOSE(***) (DN**mm) W.P.**BAR/**PSI *Q/****(YEAR)

NORMS	COLOUR
	  
	YELLOW BLACK RED